



NEW!

SEP 60 ST

Condensate
cleaner



Disposable condensate cleaner for compressor system capacities of up to 60cfm (1.7 m³/min or 11kW)

Only SEPURA gives you this performance from such a small package. Our new **STERLING** filter medium gives **SEP 60 ST** the capacity to out-perform separators 4 times its size. And it's pure simplicity to install and replace. Just fix the permanent back plate to a wall or cabinet, insert two push-in fittings and it starts to protect you—and the environment. Oily water in; clean water out. Discharge straight to the sewer (as low as 5ppm oil-in-water) —legally*

At the end of its service life, remove the push fittings, attach the clip-on lid and plug (provided with the replacement unit) and slide it off the wall plate. Sealed, outwardly clean and ready for disposal.

- Compressor capacity up to 60cfm (1.7 m³/min).
- Service life - 5000 operating hours at 60cfm (replace annually) or 8000 hours at 30cfm (replace every 2 years)**
- Dimensions only 145mm x 145mm x 220mm approx
- Wall or cabinet mounting (re-useable plate provided)
- Push-in connections for speed and ease
- Cleanest possible servicing routine
- Disposable. Clip-on cap and blanking plug seal the retained oil inside the cleaner for transit.
- Lightweight and compact for international bulk shipping

Condensate Systems Ltd

2 Delta Way Business Park
Longford Rd, Bridgtown, Cannock
Staffordshire
WS11 0LJ

tel: 0044(0)1543 378402 fax: 0044 (0)1543 578202
Email: sales@oil-water.com Web: www.oil-water.com

**It is the user's responsibility to verify discharge allowances in his/her region
**Assumes compressor oil carry-over is no more than 5mg/m³*

